

# ROBAN Banner Vinyls

IJet Premium Latex  
Single Sided Banners  
LX510

IJET PREMIUM LATEX is a UV resistant, PVC coated, smooth satin surfaced reinforced banner vinyl exhibiting a scrimless appearance after printing. It is ideal for closely viewed, high resolution images used in high strength indoor or outdoor sign & banner applications. It's softer coating gives a more supple & flexible feel and is dimensionally stable, draped well and is more visually appealing. This product has been engineered to suit latex printers & their ink.



Quality

Economy

Performance

► Premium

## Product information

Composition:	High tensile woven polyester yarn knife coated with PVC resin
Main Applications:	High print quality, close viewed banners
Features:	Frontlit, excellent layflat, smooth surface, high resolution, low curl.
Benefits:	Highest image quality, ease of printing, processing & durability
Formulation:	Anti-static, UV stabilized, Fire Retardant
Storage Conditions:	Store at 22°C 50 ~ 55% RH
Shelf Life:	12 months from date of manufacture
Remarks:	HP latex suitable

## Certifications

- Application
- Closely viewed, high quality banners
- Manufacturing
- ISO9001

## Weight

- 510 grams per m<sup>2</sup> ± 5%

## Stock Availability

Sheet Sizes:	See Sheet Cutting
Roll Widths (mm):	1370, 2500 & 3200
Roll Lengths (mtrs):	50
Log Cutting:	Up to 3200mm widths
Standard Core:	76mm ID
Sheet Cutting:	up to 3200mm x 1830mm

## Durability

- 🏠 6 years
- ⌚ 3 years

## Printing

Method:	Most solvent, Latex, UV curable digital & screen print systems.
Printable Sides:	One, wound facing inside of roll
Ink Suitability:	Solvent, Latex, UV & Screen

## Eco Response

- Certifications
- VCA Product Stewardship
- Heavy Metal Free
- Compliant, non-toxic
- Safety Compliance
- Reach, EN-71, RoHS

## Basic Physical Data

Thickness:	0.43mm
Weight:	510gsm
Denier & Density:	Denier 1000x1000 - Density (cm) 18 x 18
Gloss Level:	Satin

## Thermal Data

Heat Resistance:	70 °C
Cold Resistance:	-30 °C

ASK  
US

# ROBAN Banner Vinyls

IJet Premium Latex  
Single Sided Banners  
LX510



## Physical Characteristics

<b>Tearing Strength</b>	MD=20KG, CD=15KG
<b>Flame Retardant</b>	NFPA-701 DIN4102-B1
<b>Environmental</b>	EN-71, RoHS
<b>Welding Adhesion</b>	8.0 Kg/5cm
<b>Coating Adhesion</b>	142.1 N/50mm
<b>Thickness</b>	0.43 mm (16.9 mil) ± 5%
<b>Weight</b>	510 grams per m <sup>2</sup> ± 5%
<b>Yarn / Scrim</b>	Denier = 1000x1000 Dtex = 1100x1100
<b>Tensile Strength</b>	239 kg/5cm in MD, 216 kg/5cm in CD
<b>Density / Threads</b>	Per Inch = 18x18 Per cm=7x7
<b>Elongation at Break</b>	MD=25.3% CD=27%
<b>Adhesion Strength</b>	8 kgs/50mm in both MD and CD
<b>Surface Tension</b>	42 Dyne/cm <sup>3</sup>
<b>Surface Finish</b>	Satin
<b>UV Stabilized</b>	Yes

## Finishing

<b>Cutting</b>	✓
<b>Welding</b>	✓
<b>Folding</b>	✓
<b>Gluing</b>	✓
<b>Eyeletting</b>	✓
<b>Stitching</b>	✓
<b>Laminating</b>	✓
<b>Bending</b>	✓
<b>Routing</b>	X
<b>Punching</b>	✓
<b>Drilling</b>	✓
<b>Screwing</b>	✓
<b>V-Grooving</b>	X